

SAFETY DATA SHEET

Date of issue/Date of revision

: 22 March 2026

Version

: 1.12



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : HARDENER 008 7730

Product code : SDS-0087730

Other means of identification

SKU-710012180; SKU-710014653

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Professional applications, Used by spraying.

Use of the substance/mixture : Hardener.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Tikkurila Oyj
P.O. Box 53
FI-01301 VANTAA
FINLAND
Tel. +358 20 191 2000

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

Tikkurila Oyj
+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H332

Skin Sens. 1, H317

STOT SE 3, H335

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 2: Hazards identification

Hazard pictograms

:



Signal word

: Warning

Hazard statements

: May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.

Prevention

: Wear protective gloves. Avoid breathing vapour.

Response

: IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

P280, P261, P304 + P312, P362 + P364, P403 + P233, P501

Hazardous ingredients

: Hexamethylene diisocyanate, oligomers.; 2-Oxepanone, polymer with 1,6-diisocyanatohexane and 1,6-hexanediol; Hexamethylene diisocyanate, oligomers (isocyanurate type); 4-isocyanatosulphonyltoluene and hexamethylene-di-isocyanate

Supplemental label elements

: Contains isocyanates. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: As from August 24 2023 adequate training is required before industrial or professional use.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.

: Based on available data, the classification criteria are not met.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hexamethylene diisocyanate, oligomers.	EC: 500-060-2 CAS: 28182-81-2	≥25 - ≤50	Acute Tox. 4, H332 Skin Sens. 1, H317 STOT SE 3, H335	ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1]
2-Oxepanone, polymer with 1,6-diisocyanatohexane and 1,6-hexanediol	CAS: 164250-92-4	≥10 - ≤25	Acute Tox. 4, H332 Skin Sens. 1, H317 STOT SE 3, H335	ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1]
Hexamethylene diisocyanate, oligomers (isocyanurate type)	REACH #: 01-2119485796-17 EC: 931-274-8 CAS: 28182-81-2	≥10 - ≤25	Acute Tox. 4, H332 Skin Sens. 1, H317 STOT SE 3, H335	ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
4-isocyanatosulphonyltoluene	REACH #: 01-2119980050-47 EC: 223-810-8 CAS: 4083-64-1 Index: 615-012-00-7	<1.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 STOT SE 3, H335 EUH014	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5% STOT SE 3, H335: C ≥ 5%	[1]
hexamethylene-diisocyanate	REACH #: 01-2119457571-37 EC: 212-485-8 CAS: 822-06-0 Index: 615-011-00-1	<0.50	Acute Tox. 4, H302 Acute Tox. 1, H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 710 mg/kg ATE [Inhalation (vapours)] = 0.151 mg/l Resp. Sens. 1, H334: C ≥ 0.5% Skin Sens. 1, H317: C ≥ 0.5%	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 5: Firefighting measures

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
Cyanate and isocyanate.
hydrogen cyanide

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

Special provisions : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 6: Accidental release measures

according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
- See Section 8 for information on appropriate personal protective equipment.
- See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

- : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Precautions should be taken to minimise exposure to atmospheric humidity or water. CO₂ will be formed, which, in closed containers, could result in pressurisation.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
n-butyl acetate	EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm.
hexamethylene-di-isocyanate	EU OEL (Europe, 3/2024) [diisocyanates] Absorbed through skin , Skin sensitiser , Inhalation sensitiser. STEL 15 minutes: 20 µg/m ³ (as isocyanates functional groups of the

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 8: Exposure controls/personal protection

diisocyanate compounds.).
TWA 8 hours: 10 µg/m³ (as isocyanates functional groups of the diisocyanate compounds.).

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value
Hexamethylene diisocyanate, oligomers.	DNEL - Workers - Long term - Inhalation <i>Local</i>	0.5 mg/m ³
	DNEL - Workers - Short term - Inhalation <i>Local</i>	1 mg/m ³
Hexamethylene diisocyanate, oligomers (isocyanurate type)	DNEL - Workers - Long term - Inhalation <i>Local</i>	0.5 mg/m ³
	DNEL - Workers - Short term - Inhalation <i>Local</i>	1 mg/m ³
n-butyl acetate	DNEL - Workers - Long term - Inhalation <i>Systemic</i>	300 mg/m ³
	DNEL - Workers - Long term - Dermal <i>Systemic</i>	11 mg/m ³
	DNEL - General population - Long term - Oral <i>Systemic</i>	2 mg/kg bw/day
	DNEL - General population - Short term - Oral <i>Systemic</i>	2 mg/kg bw/day
	DNEL - General population - Long term - Dermal <i>Systemic</i>	3.4 mg/kg bw/day
	DNEL - General population - Short term - Dermal <i>Systemic</i>	6 mg/kg bw/day
	DNEL - Workers - Long term - Dermal <i>Systemic</i>	7 mg/kg bw/day
	DNEL - Workers - Short term - Dermal <i>Systemic</i>	11 mg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Systemic</i>	12 mg/m ³
	DNEL - General population - Long term - Inhalation <i>Local</i>	35.7 mg/m ³
	DNEL - Workers - Long term - Inhalation <i>Systemic</i>	48 mg/m ³
	DNEL - General population - Short term - Inhalation <i>Local</i>	300 mg/m ³
	DNEL - General population - Short term - Inhalation <i>Systemic</i>	300 mg/m ³
	DNEL - Workers - Long term - Inhalation <i>Local</i>	300 mg/m ³
4-isocyanatosulphonyltoluene	DNEL - Workers - Short term - Inhalation <i>Local</i>	600 mg/m ³
	DNEL - Workers - Short term - Inhalation <i>Systemic</i>	600 mg/m ³
	DNEL - General population - Long term - Oral <i>Systemic</i>	0.46 mg/kg bw/day
	DNEL - General population - Long term - Dermal <i>Systemic</i>	0.46 mg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Systemic</i>	0.8 mg/m ³
	DNEL - Workers - Long term - Dermal <i>Systemic</i>	0.92 mg/kg bw/day
hexamethylene-di-isocyanate	DNEL - Workers - Long term - Inhalation <i>Systemic</i>	3.24 mg/m ³
	DNEL - Workers - Long term - Inhalation <i>Local</i>	0.035 mg/m ³
	DNEL - Workers - Short term - Inhalation <i>Local</i>	0.07 mg/m ³

PNECs

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Compartment Detail - Method	Value
Hexamethylene diisocyanate, oligomers (isocyanurate type)	Fresh water - Assessment Factors	0.127 mg/l
	Marine water - Assessment Factors	0.0127 mg/l
n-butyl acetate	Sewage Treatment Plant - Assessment Factors	88 mg/l
	Fresh water sediment - Equilibrium Partitioning	266701 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	26670 mg/kg dwt
	Soil - Equilibrium Partitioning	53182 mg/kg
	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine water sediment	0.0981 mg/kg
	Sewage Treatment Plant	35.6 mg/l
	Soil	0.0903 mg/kg
4-isocyanatosulphonyltoluene	Fresh water - Assessment Factors	0.03 mg/l
	Marine water - Assessment Factors	0.003 mg/l
	Sewage Treatment Plant - Assessment Factors	0.4 mg/l
	Fresh water sediment - Equilibrium Partitioning	0.172 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.017 mg/kg dwt
	Soil - Equilibrium Partitioning	0.017 mg/kg dwt
hexamethylene-di-isocyanate	Fresh water - Assessment Factors	0.0774 mg/l
	Marine water - Assessment Factors	0.00774 mg/l
	Sewage Treatment Plant - Assessment Factors	8.42 mg/l
	Fresh water sediment - Equilibrium Partitioning	0.01334 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.001334 mg/kg dwt
	Soil - Equilibrium Partitioning	0.0026 mg/kg dwt

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety glasses with side shields. Use eye protection according to EN 166.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 8: Exposure controls/personal protection

- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use an air-fed respirator unless a site-specific assessment determines that an air-fed respirator is not necessary, in which case the results of the risk assessment should be utilized to determine whether respiratory protection is necessary and what type of protection is appropriate. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Restrictions on use** : Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Colourless to light yellow.
- Odour** : Characteristic.
- Melting point/freezing point** : Not determined.
- Boiling point or initial boiling point and boiling range** : >37.78°C
- Flammability** : Not determined. There are no data available on the mixture itself.
- Lower and upper explosion limit** : Not available.
- Flash point** : Closed cup: Not applicable.
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
n-butyl acetate	415	779	EU A.15

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm²/s
- Solubility** :

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 9: Physical and chemical properties

Media	Result
cold water	Not soluble

Partition coefficient n-octanol/ water (log Pow) : Not applicable.

Vapour pressure

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
n-butyl acetate	11.25096	1.5	DIN EN 13016-2			

Relative density : 1.06

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : In a fire, hazardous decomposition products may be produced.
Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from: oxidising agents, strong alkalis, strong acids, amines, alcohols, water. Uncontrolled exothermic reactions occur with amines and alcohols.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: Cyanate and isocyanate. carbon oxides nitrogen oxides hydrogen cyanide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Harmful if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

Acute toxicity

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 11: Toxicological information

Product/ingredient name	Result	Dose / Exposure
Hexamethylene diisocyanate, oligomers.	Rat - Female - Oral - LD50	>2500 mg/kg
2-Oxepanone, polymer with 1,6-diisocyanatohexane and 1,6-hexanediol	Rabbit - Dermal - LD50	>2000 mg/kg
	Rat - Oral - LD50	>5000 mg/kg
Hexamethylene diisocyanate, oligomers (isocyanurate type)	Rat - Inhalation - LC50 Dusts and mists	1.5 mg/l [4 hours]
	Rat - Female - Oral - LD50	>2500 mg/kg
n-butyl acetate	Rabbit - Dermal - LD50	>2000 mg/kg
	Rabbit - Dermal - LD50	>17600 mg/kg
4-isocyanatosulphonyltoluene	Rat - Oral - LD50	10.768 g/kg
	Rat - Inhalation - LC50 Vapour	2000 ppm [4 hours]
	Rat - Inhalation - LC50 Vapour	>21.1 mg/l [4 hours]
	Rat - Oral - LD50	2234 mg/kg
hexamethylene-di-isocyanate	<i>Toxic effects:</i> Gastrointestinal - Other changes	
	Rat - Oral - LD50	0.71 g/kg
	Rabbit - Dermal - LD50	0.57 g/kg
	Rat - Inhalation - LC50 Vapour	151 mg/m ³ [4 hours]
	Rat - Inhalation - LC50 Dusts and mists	124 mg/m ³ [4 hours]

Acute toxicity estimates

Route	ATE value
Inhalation (vapours)	46.98 mg/l
Inhalation (dusts and mists)	1.59 mg/l

Conclusion/Summary : Harmful if inhaled.

Irritation/Corrosion

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Product/ingredient name	Test	Result
2-Oxepanone, polymer with 1,6-diisocyanatohexane and 1,6-hexanediol	Guinea pig - skin OECD 406	Sensitising

Conclusion/Summary

Skin : May cause an allergic skin reaction.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
Hexamethylene diisocyanate, oligomers.	Category 3	-	Respiratory tract irritation
2-Oxepanone, polymer with 1,6-diisocyanatohexane and 1,6-hexanediol	Category 3	-	Respiratory tract irritation
Hexamethylene diisocyanate, oligomers (isocyanurate type)	Category 3	-	Respiratory tract irritation
n-butyl acetate	Category 3	-	Narcotic effects
4-isocyanatosulphonyltoluene	Category 3	-	Respiratory tract irritation
hexamethylene-di-isocyanate	Category 3	-	Respiratory tract irritation

Conclusion/Summary

May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Harmful if inhaled. May cause respiratory irritation.

Ingestion : No known significant effects or critical hazards.

Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing

Ingestion : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 11: Toxicological information

- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.
- Other information** : Prolonged or repeated contact may dry skin and cause irritation. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitisation of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Persons with a history of skin sensitisation problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Repeated exposure may lead to permanent respiratory disability. Moisture-sensitive material. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
Hexamethylene diisocyanate, oligomers.	Acute - LC50	Fish - <i>Danio rerio (zebra fish)</i>	>100 mg/l [96 hours]
	Acute - EC50	Daphnia - <i>daphnia magna</i>	>100 mg/l [48 hours]
	Acute - EC50	Algae - <i>scenedesmus subspicatus</i>	>1000 mg/l [72 hours]
Hexamethylene diisocyanate, oligomers (isocyanurate type)	Acute - LC50	Fish - <i>Danio rerio (zebra fish)</i>	>100 mg/l [96 hours]
	Acute - EC50	Daphnia - <i>daphnia magna</i>	>100 mg/l [48 hours]
	Acute - EC50	Algae - <i>scenedesmus subspicatus</i>	>1000 mg/l [72 hours]
n-butyl acetate	Acute - LC50	Fish	18 mg/l [96 hours]

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose / Inoculum
n-butyl acetate	TEPA and OECD 301D	83% [28 days] - Readily	

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hexamethylene diisocyanate, oligomers.	-	-	Not readily
2-Oxepanone, polymer with 1,6-diisocyanatohexane and 1,6-hexanediol	-	-	Not readily
Hexamethylene diisocyanate, oligomers (isocyanurate type)	-	-	Not readily
n-butyl acetate	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Hexamethylene diisocyanate, oligomers.	5.54	3.2	Low
Hexamethylene diisocyanate, oligomers (isocyanurate type)	5.54	3.2	Low
n-butyl acetate	2.3	-	Low
hexamethylene-di-isocyanate	0.02	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
n-butyl acetate	1.5	33.2139
4-isocyanatosulphonyltoluene	1.5	31.6836
hexamethylene-di-isocyanate	1.4	23.8009

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 13: Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste :

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : None identified.

ADN : None identified.

IMDG : None identified.

IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 14: Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
HARDENER 008 7730 hexamethylene-di-isocyanate	3 74

Labelling : As from August 24 2023 adequate training is required before industrial or professional use.

Other EU regulations

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

Code : SDS-0087730

Date of issue/Date of revision

: 22 March 2026

HARDENER 008 7730

SECTION 16: Other information

IATA = International Air Transport Association

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH014	Reacts violently with water.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 1	ACUTE TOXICITY - Category 1
Acute Tox. 4	ACUTE TOXICITY - Category 4
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 22 March 2026

Date of previous issue : 10 November 2025

Prepared by : EHS

Version : 1.12

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.