



TIKKURILA

# HELMI FURNITURE LACQUER 10

SEMI-MATT DURABLE TINTABLE FURNITURE LACQUER.

**DESCRIPTION**

Semi-matt water-borne, non-yellowing, tintable acrylic lacquer for indoor use.

**RECOMMENDED USES**

Furniture such as tables, chairs, bookshelves, etc., toys, panel walls, wooden ceilings, doors and similar wood surfaces. Also suitable for the protective lacquering of stained surfaces.

**PRODUCT FEATURES**

For wood surfaces in dry interior spaces according to instructions. Not suitable for treating floors (use Parketti-Ässä floor lacquer for lacquering floors).



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

## HELMI FURNITURE LACQUER 10

TECHNICAL DATA	
<b>Base paints</b>	EP BASE
<b>Colour Shades</b>	<b>Color cards:</b> Tikkurila Timeless Translucent, Deco Grey colour card Can be tinted in Tikkurila translucent colors.
<b>Gloss</b>	Semi-matt.
<b>Coverage</b>	8–14 m <sup>2</sup> /l. Actual spreading rate depends on the type, porosity and hardness of the wood.
<b>Can sizes</b>	0.225 l, 0.9 l, 2.7 l
<b>Thinner</b>	Water
<b>Application method</b>	Brush, sponge or spray.
<b>Drying time</b>	Dust dry in approx. 1/2 hour. Sandable and recoatable after 2–3 hours. Ready for use the following day. The lacquered surface will reach its final hardness after approx. two weeks. Avoid hard stresses, cleaning and placing of sticking and hot objects on the lacquered surface during this time.
<b>Density (kg/l)</b>	approx. 1.0 kg/l, ISO 2811
<b>Chemical resistance</b>	Resistant to cleaning chemicals and mild solvents, such as white spirit. Any colored stains from coffee, tea, etc. must be wiped off immediately. Well resistant to oils and greases.
<b>Volume solids (%)</b>	32
<b>VOC</b>	(cat A/e) 130g/l(2010) Kiva contains VOCmax. 130 g/l.
<b>Storage</b>	Protect from frost. Protect from frost

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



# HELMİ FURNITURE LACQUER 10

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be treated must be dry, the ambient temperature at least +10 °C and the relative humidity of air 30–80%.

### Surface preparation

Bare wooden surface:

Clean the wood surface of any dirt and dust. Wet the surface lightly with water, let dry and sand off the loose wood fibers. Remove the sanding dust.

Previously lacquered wooden surfaces:

Wash the surface with Maalipesu detergent and rinse carefully with water. Sand the surface matte. If the lacquered surface is in very poor condition, remove it completely with a paint remover or by sanding. Treat it as a new wood surface.

### Lacquering

Stir Helmi Furniture Lacquer 30 thoroughly down to the bottom before and occasionally during use. Thin with water, if necessary. Apply 2–3 coats by brush, sponge or spray.

If you are using a tinted product, first test the product on a separate piece of wood to ensure that you have the right color. The final color of the treated surface depends on the type, hardness and original color of the wood and the number of coats. Thin the tinted lacquer approx. 20–30% with water for the first coat. Usually, the desired color and level of gloss can be achieved after applying two coats. Always treat the surfaces without interruptions and, with large panel surfaces, a few boards at a time in order to achieve a uniform color.

### Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint. Remove excess paint from tools. Clean tools with water. Tikkurila Pensselipesu (Tool Cleaner) is recommended to be used to remove a bit hardened paint.

### Maintenance instructions

If needed, after approx. two weeks from applying the lacquer, at the earliest:

Clean the surface lightly with a damp cleaning tool, soft brush, sponge or cleaning cloth and a neutral (pH 6–8) detergent. Do not leave the surface wet. Clean very dirty surfaces with a mild alkaline (pH 8–10) cleaning solution and e.g. a cleaning cloth or sponge. Rinse the surface carefully.

### Maintenance treatment

Surfaces lacquered with Helmi Furniture Lacquer 30 lacquer can be treated with a similar water-borne lacquer or Helmi Furniture Lacquer 30. Apply 1-2 coats by brush, sponge or spray. See Pretreatment.

### Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

### Health and Safety

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. Wear protective gloves. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



# HELMI FURNITURE LACQUER 10

product during storage. Contains: C(M)IT/MIT (3:1) and BIT.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.