



TIKKURILA

PANEELIKATTO VALKOINEN

WHITE PANEL CEILING PAINT

DESCRIPTION Water-borne acrylate paint for panel ceilings.

RECOMMENDED USES Paneled ceilings.

PRODUCT FEATURES For new and old paneled ceilings in dry interiors. Also suitable for repainting previously painted or lacquered paneled ceilings.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



PANEELIKATTO VALKOINEN

TECHNICAL DATA

Colour Shades	Color: White
Gloss	Matt.
Coverage	6 m ² /l
Can sizes	3 l, 10 l
Application method	Brush
Drying time	Touch-dry in approximately one hour. Recoatable in approximately two hours.
Density (kg/l)	1.3 kg/l, ISO 2811
Volume solids (%)	36
Storage	Protect from frost. Protect from frost

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

PANEELIKATTO VALKOINEN

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the ambient temperature at least +8 °C and the relative humidity of air below 80%. A low temperature (approx. +15°C) and higher humidity (50–70% RH) will extend the working time and make application easier.

Surface preparation

In order to ensure the best possible adhesion, clean new surfaces of possible dirt and dust. Apply one or two coats of Multistop sealing primer over knotty and darkened panels.

Wash painted or varnished surfaces with Maalipesu according to the instructions on the label. Allow to dry. Remove any loose paint or lacquer with a scraper and sand the entire surface. Remove the sanding dust. If necessary, use Presto Rapid Filler to fill any cracks and dents and sand the filled areas. Remove the sanding dust.

Painting

Stir Paneelikatto Valkoinen carefully before use. The product is used without thinning. Apply 1–2 generous coats with a synthetic-fiber brush. Apply the first coat to new panels separately before installation. Apply the paint thinly on joints.

Cleaning of tools

Clean tools with water. Remove excess paint/ lacquer from tools and clean with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint. Remove excess paint from tools. Clean tools with water. Tikkurila Pensselipesu (Tool Cleaner) is recommended to be used to remove a bit hardened paint.

Maintenance instructions

Under normal conditions, the product will achieve its final hardness and durability in one month. Therefore, the surfaces must be handled with care for a few weeks. If required after one month from painting, but no earlier, clean the surface with neutral (pH 6–8) dish-washing liquid solution and a soft brush, sponge or cloth. Clean soiled surfaces with a mild alkaline (pH 8–10) detergent solution and, for example, a cloth, mop or sponge. Rinse the surface carefully.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Wear protective gloves. Contains 1,2-benzisothiazol-3(2H)-one (BIT). May produce an allergic reaction.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.