

TIKKURILA

TIKKURILA TUNTURIPAJU

MATT INTERIOR WALL PAINT

DESCRIPTION	Matt interior wall paint. Earthy, muted green.
RECOMMENDED USES	For painting ceilings and walls in dry interior spaces.
PRODUCT FEATURES	For interior painting. Suitable for plaster, concrete, filler-treated, brick, cardboard, wood surfaces, cardboard-covered plasterboard, chipboard and wood fiberboard. Suitable for both new and previously painted surfaces.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

TIKKURILA TUNTURIPAJU

TECHNICAL DATA

Colour Shades	Ready-made shade M495 Arctic Willow.
Gloss	Matt.
Coverage	Theoretical coverage 8-11 m²/l. Practical coverage depends on the application method, conditions, absorbency and roughness of the surface to be treated.
Can sizes	4 l
Application method	Roller, spray or brush. Airless spraying: -nozzle 0.017"–0.021" -thinning 0–10% by volume
Drying time	Dust dry after 30 minutes. Recoatable after 1-2 hours.
Density (kg/l)	approx. 1.3 kg/l, ISO 2811.
Chemical resistance	Withstands cleaning chemicals and weak solvents, such as white spirit.
Wet scrub resistance	approx. 1.3 kg/l, ISO 2811.
Volume solids (%)	37
VOC	(cat A/a) 30g/l (2010) Tikkurila Tunturipaju contains VOC max. 10g/l.
Storage	Must be protected from frost. Store in a dry and cool place, protected from sunlight. Tinted paint or opened container does not withstand long-term storage. Close the can carefully for the next use.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

TIKKURILA TUNTURIPAJU

APPLICATION INSTRUCTIONS

Application conditions
The surface to be painted must be dry, the ambient temperature at least +10 °C and the relative humidity of air below 80%.

Surface preparation
Unpainted surfaces:

Clean the new surfaces by removing any dirt and dust. If necessary, level the surfaces with a suitable Presto filler and sand the dried surface. Remove the sanding dust. Prime with Varma primer, for example.

Previously painted surfaces:

Wash surfaces with Seinäpesu detergent. Sand the painted surfaces non-glossy. Remove the sanding dust. Fill any cracks and holes with a suitable Presto filler and sand the dried surface. Remove the sanding dust. If necessary, prime with e.g. Varma primer before applying the top coat.

Painting
Stir the paint well before use and thin with water, if necessary. Apply 1–2 coats by roller, brush or spray.

Cleaning of tools
Clean the tools with water and soap Remove excess paint/ lacquer from tools and clean with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Maintenance instructions
If needed, after approx. 1 month from treating the surface, at the earliest.

Clean the surfaces with a neutral (pH 6–8) cleaning solution and e.g. a sponge or cleaning cloth. Clean very dirty surfaces with a mild alkaline (pH 8–10) cleaning solution and e.g. a cleaning cloth or sponge. After washing, rinse the surface thoroughly. Follow the dilution instructions given by the detergent manufacturer when mixing the cleaning solution.

After surface treatment, surfaces must be handled with care for a few weeks, as the product will reach its final hardness and durability after about a month under normal conditions. If the surfaces need to be cleaned soon after finishing, clean them lightly with a damp cleaning cloth.

Maintenance treatment
Painted surfaces can be maintenance painted with same or same kind of waterborne paint. See Preparation.

Environmental protection and waste disposal
Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Do not dispose paint or rinse painting tools in sinks or drains.

Health and Safety
The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: BIT and C(M)IT/MIT (3:1).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.